

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 May 2004 (27.05.2004)

PCT

(10) International Publication Number
WO 2004/044945 A1

(51) International Patent Classification⁷: **H01K 9/08**,
9/00, B60Q 1/04

(74) Agent: **KIM, Hee-So**; 2F Daeho Building, 1502-12, Seo-
cho 3-dong, Seocho-gu, 137-870 Seoul (KR).

(21) International Application Number:
PCT/KR2003/002420

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date:
11 November 2003 (11.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(30) Priority Data:
10-2002-0069678
11 November 2002 (11.11.2002) KR

(71) Applicants and


(72) Inventors: **CHON, Young-Il** [KR/KR]; 106-103
Haenuri-Sunkyung Apartment, 1363-1, Ssangyong 2-dong,
330-760 Cheonan-si, Chungcheongnam-do (KR). **CHON,**
Sang-Wook [KR/KR]; 106-103 Haenuri-Sunkyung Apart-
ment, 1363-1, Ssangyong 2-dong, 330-760 Cheonan-si,
Chungcheongnam-do (KR).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS AND METHOD FOR CONTROLLING HEADLIGHT IN VEHICLE AND HEADLIGHT LAMP HAV-
ING MULTIFUNCTION STRUCTURE



300

(57) Abstract: The present invention relates to a headlight lamp (110) having a multifunction structure in which a lighting angle of a headlight of a vehicle is automatically and manually controlled based on a running speed of a vehicle, a brightness of a headlight of an opponent vehicle and a surrounding brightness of a vehicle. The headlight lamp (110) includes a plurality of high angle headlight filaments (115), capable of lighting for providing a high angle beam to a vehicle, a plurality of low angle headlight filaments (111) capable of lighting for providing a low angle beam to the vehicle, low angle headlight reflection covers (112) provided in the low angle headlight filaments (111) respectively, for thereby allowing the light from the low angle headlight filaments (111) to have a low beam pattern angle, and external connection terminals.

WO 2004/044945 A1